SAFETY DATA SHEET- BRAKE KLEEN



Section 1: Identification of the Substance/Mixture and of the Supplier

Product Name: 1425 Solvent

Proper Shipping Name Flammable liquid, n.o.s.

Recommended use: Solvent Cleaner **Restriction of use:** Refer to Section 15

Company Details Marketing Chemicals Ltd

Address: 7 Rymer Place, Mangere Bridge

Auckland. New Zealand

Emergency Telephone: +64 274 340990(24 hours)

National Poison Center(24 hours): 0800 POISON [764 766]

Telephone: +64 9 634 3862 [8.00 am to 4.30pm – Monday to Friday]

Fax: +64 9 634 3864

Date of preperation 29 August 2024 v2

Section 2: Hazard Identification

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

Pictograms:



EPA Approval Number: Cleaning Products (Flammable) – HSR002528

Signal Word: DANGER

| GHS Category | Hazard Code | Hazard Statement |
|---|-------------|--|
| Flammable Liquids Cat. 3 | H226 | Flammable liquid and vapour. |
| Aspiration hazard Cat. 1 | H304 | May be fatal if swallowed and enters airways. |
| Skin irritation Cat. 2 | H315 | Causes skin irritation. |
| Reproductive toxicity Cat. 2 | H361 | Suspected of damaging fertility or the unborn child. |
| specific target organ toxicity - single exposure Cat 3 - Narcotic Effects | H336 | May cause drowsiness or dizziness. |
| Hazardous to the aquatic environment chronic Cat. 2 | H411 | Toxic to aquatic life with long lasting effects. |

| Prevention Code | Prevention Statement |
|------------------------|---|
| P102 | Keep out of reach of children. |
| P103 | Read label before use. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P210 | Keep away from heat, sparks, open flames and hot surfaces. No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical, ventilating, and lighting. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P261 | Avoid breathing dust, fumes, gas, mist, vapours or spray. |
| P264 | Wash hands thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective clothing as detailed in SDS Section 8. |
| Response code | Response Statement |
| P101 | If medical advice is needed, have product container or label at hand. |
| P312 | Call a POISON CENTER or doctor/physician if you feel unwell. |
| P331 | Do NOT induce vomiting. |
| P391 | Collect spillage. |
| P301 + P310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. |
| P303 + | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. |
| P361+P353 | Rinse skin with water/shower. |
| P304 + P340 | IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. |
| P308 + P313 | IF exposed or concerned: Get medical advice/ attention. |
| P332 + P313 | If skin irritation occurs: Get medical advice/ attention. |
| P362+P364 | Take off contaminated clothing and wash before reuse. |
| P370 + P378 | In case of a fire use CO2, Dry Chemical or Foam. |
| Storage Code | Storage Statement |
| P405 | Store locked up. |
| P403 + P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403 + P235 | Store in a well-ventilated place. Keep cool. |

Section 3: Composition/Information on Ingredients

| Name | Concentration % | CAS Number |
|-------------------------------------|-----------------|------------|
| Petroleum Naptha Hydrotreated Light | > 60 | 64742-49-0 |

Note: Manufacturer has provided full ingredient information for assessment.

Section 4: First Aid Measures

Eyes: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice/attention.

Skin: Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. If skin irritation occurs: Get medical advice/

attention.

Ingestion: If medical advice is needed, have product container or label at hand.

Call a POISON CENTER or doctor/physician if you feel unwell.

Do NOT induce vomiting.

Inhalation: Remove from contaminated area. Get medical advice/attention if you

feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion: Nausea, vomiting & sweating with burns to the mouth & oesophagus may occur.

Unconciousness may follow

Inhalation: The vapour is discomforting to the upper respiratory tract and lungs and may be

harmful if inhaled. Dizziness & shortness of breath occur from mild poisoning.

Skin: Possible irritation on sensitive skin

Eye: Irritation

FOR FURTHER INFORMATION CONTACT (24 hours) THE NATIONAL POISON CENTRE: 0800 POISON [764 766]

Section 5: Fire Fighting Measures

Hazard Type Flammable Liquid

Oxides of Carbon when burned. **Hazards from products**

Suitable Extinguishing

media

CO2, Dry Chemical or Foam. Water spray or Fog (for large fires only)

Precautions for firefighters

and special protective

clothing

Full respiration equipment is advisable. Evacuate area.

3Y **HAZCHEM CODE**

Section 6: Accidental Release Measures

Land Spills or Leaks:

Wear protective clothing as detailed in Section 8. Remove all unnecessary personnel. Eliminate ignition sources. Contain spill with inert material & place in recovery containers for disposal. Avoid release

to the environment.

Waste Disposal Method: Dispose through Licensed Disposal Company

Section 7: Handling And Storage

Handling

- Keep out of reach of children.
- Read label before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames and hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical, ventilating, and lighting.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid release to the environment.
- Wear protective clothing.
- Use personal protective equipment as required.

Storage:

- Store in a well-ventilated place. Keep cool.
- Keep out of reach of children.
- Store locked up.
- Protect containers against physical damage and check regularly for leaks.

Section 8: Exposure Controls/Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

TWA STEL Substance ppm mg/m³ ppm mg/m³

No ingredients have exposure limits

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices Nov 2023 14TH EDITION.

Personal Protection Equipment







Engineering Controls: Local exhaust ventilation usually required

Eye / Face Protection: Safety glasses with a side shield or a full-face shield should be worn.

Body Protection: Overalls / PVC apron

Respiratory Protection: Self contained Breathing apparatus required if using in a confined space

Section 9: Physical And Chemical Properties

| Appearance | Liquid |
|----------------------------------|--|
| Colour | Water white |
| Odour | Solvent Odour |
| Odour Threshold | Not available |
| pН | Not applicable |
| Boiling Point | 85°C |
| Melting Point | Not available |
| Freezing Point | Not available |
| Flash Point | -22 ^o C (cup closed) |
| Flammability | Flammable |
| Upper and Lower Explosive | 1% to 6.0% |
| Limits | |
| Vapour Pressure | <35 |
| Vapour Density | 4.8 |
| Specific Gravity | 0.70 g/cm ³ @ 25 ⁰ C |
| Solubility in Water | Insoluble |
| Partition Coefficient: | Not available |
| Auto-ignition Temperature | 280°C |
| Decomposition Temperature | Not available |
| Kinematic Viscosity | Not available |
| Particle Characteristics | Not applicable |
| Volatiles | 100% |

Section 10: Stability And Reactivity

Conditions Contributing to

Instability:

Not available.

Incompatibility: Sources of heat &/or ignition, Oxidising agents.

Hazardous Decomposition

Products:

Carbon Dioxide & Water

Conditions Contributing to Hazardous Polymerization

Will not polymerise

Section 11: Toxicological Information

Acute Effects:

| Swallowed | This product is not classified as acutely toxic. |
|------------|---|
| Dermal | This product is not classified as acutely toxic. |
| Inhalation | This product is not classified as acutely toxic. |
| Eye | This product is not classified an eye irritant/corrosive. |
| Skin | Causes skin irritation. |

Safety Data Sheet- 1425 Solvent

Chronic Effects:

| Carcinogenicity | This product is not classified as carcinogenic. | |
|-----------------------|--|--|
| Reproductive Toxicity | Suspected of damaging fertility or the unborn child. | |
| | | |
| Germ Cell | This product is not classified as mutagenic. | |
| Mutagenicity | | |
| Aspiration | May be fatal if swallowed and enters airways. | |
| STOT/SE | May cause drowsiness or dizziness. | |
| STOT/RE | This product is not classified as STOT RE. | |

Section 12: Ecological Information

Toxic to aquatic life with long lasting effects

Environmental Precautions: Do not allow product to wash into waterways.

| Persistence and degradability | No data available |
|-------------------------------|-------------------|
| Bioaccumulation | No data available |
| Mobility in Soil | No data available |
| Other adverse effects | No data available |

Section 13: Disposal Considerations

Recover and recycle product whenever possible. Dispose of waste in accordance with Regional Authority or local council bylaws.

Ensure empty containers are vented and dry. Residues may cause an explosion hazard. Do not puncture, cut or weld un-cleaned drums. Send clean dry drums to recycler or metal scrap re-claimer. Do not use empty drums for storing other products.

Section 14: Transport Information

This product is classified as a Dangerous Good for transport in NZ; NZS 5433:2020 and SNZ HB 5433:2021



Road, Rail, Sea and Air Transport

| UN No | 1993 | |
|---------------------------|---|--|
| Class - Primary | 3 | |
| Packing Group | II | |
| Proper Shipping Name | FLAMMABLE LIQUID, N.O.S. | |
| Marine Pollutant | Yes | |
| Special Provisions | If the product's individual container is below 1L, it can be transported as | |
| | a non-DG as long as the product packaging is still labelled as per DG | |
| | requirements and the driver is given safety information in accordance | |
| | with Chapter 3.4 of the UNRTDG. | |

Section 15: Regulatory Information

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval Code: Cleaning Products (Flammable) - HSR0002528

| HSW (HS) Regulations 2017 and EPA Notices | Trigger Quantity |
|---|----------------------------------|
| Certified Handler | Not required |
| Location Certificate | 100L (>5L), 250L (<5L), 50L open |
| Tracking Trigger Quantities | Not required |
| Signage Trigger Quantities | 250L |
| Emergency Response Plan | 1000L |
| Secondary Containment | 1000L |
| Fire Extinguishers | 2 x >250L |
| Restriction of Use | None |

Section 16: Other Information

Glossary

EC50Median effective concentration.EELEnvironmental Exposure Limit.EPAEnvironmental Protection Authority

HSNO Hazardous Substances and New Organisms.

HSW Health and Safety at Work.

LC₅₀ Lethal concentration that will kill 50% of the test organisms inhaling or

ingesting it.

LD₅₀ Lethal dose to kill 50% of test animals/organisms.

LEL Lower explosive level.

OSHA American Occupational Safety and Health Administration.

TEL Tolerable Exposure Limit.

TLV Threshold Limit Value-an exposure limit set by responsible authority.

UEL Upper Explosive Level WES Workplace Exposure Limit

References:

- 1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
- 2. Workplace Exposure Standards and Biological Exposure Indices Nov 2023 14th edition.
- 3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
- 4. Transport of Dangerous goods on land NZS 5433:2020
- 5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

Marketing Chemicals Ltd has taken care in compiling this information. No liability is accepted directly or indirectly from its application as conditions of use are outside the Company's control. End users are obliged to conform to relevant Local Government regulations.

For General Information: Marketing Chemicals Ltd,

Phone: +64 (09) 634 3862 / +64 274 340990

Fax : +64 (09) 634 3864

Issue Date: 29 August 2024 Review Date: 29 August 2029

End of Safety Data Sheet.