# SAFETY DATA SHEET- BRAKE KLEEN



### Section 1: Identification of the Substance/Mixture and of the Supplier

**Product Name:** Air Dry Solvent

**Proper Shipping Name** Flammable liquid, n.o.s.

**Recommended use:** Solvent Cleaner **Restriction of use:** Refer to Section 15

Company Details Marketing Chemicals Ltd

**Address:** 7 Rymer Place, Mangere Bridge

Auckland. New Zealand

**Emergency Telephone:** +64 274 340990(24 hours)

National Poison Center(24 hours): 0800 POISON [ 764 766]

**Telephone:** +64 9 634 3862 [8.00 am to 4.30pm – Monday to Friday]

**Fax:** +64 9 634 3864

**Date of preperation** 29 August 2024 v2

### **Section 2: Hazard Identification**

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice  $2020\,$ 

#### **Pictograms:**



**EPA Approval Number:** Cleaning Products (Flammable) – HSR002528

#### Signal Word: DANGER

GHS Category	<b>Hazard Code</b>	Hazard Statement
Flammable Liquids Cat. 3	H226	Flammable liquid and vapour.
Aspiration hazard Cat. 1	H304	May be fatal if swallowed and enters
		airways.
Skin irritation Cat. 2	H315	Causes skin irritation.
Reproductive toxicity Cat. 2	H361	Suspected of damaging fertility or the unborn child.
specific target organ toxicity - single exposure Cat 3 - Narcotic Effects	H336	May cause drowsiness or dizziness.

Hazardous to the aquatic environment chronic Cat. 2

H411 Toxic to aquatic life with long lasting effects.

P102 Keep out of reach of children. P103 Read label before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating, and lighting. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust, fumes, gas, mist, vapours or spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment.	<b>Prevention Code</b>	Prevention Statement
P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating, and lighting. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust, fumes, gas, mist, vapours or spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.	P102	Keep out of reach of children.
P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating, and lighting. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust, fumes, gas, mist, vapours or spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.	P103	Read label before use.
P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating, and lighting. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust, fumes, gas, mist, vapours or spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.	P202	Do not handle until all safety precautions have been read and understood.
P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating, and lighting. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust, fumes, gas, mist, vapours or spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.	P210	Keep away from heat, sparks, open flames and hot surfaces. No smoking.
P241 Use explosion-proof electrical, ventilating, and lighting. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust, fumes, gas, mist, vapours or spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.	P233	Keep container tightly closed.
P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust, fumes, gas, mist, vapours or spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.	P240	Ground/bond container and receiving equipment.
P243 Take precautionary measures against static discharge. P261 Avoid breathing dust, fumes, gas, mist, vapours or spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.	P241	Use explosion-proof electrical, ventilating, and lighting.
P261 Avoid breathing dust, fumes, gas, mist, vapours or spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.	P242	Use only non-sparking tools.
P261 Avoid breathing dust, fumes, gas, mist, vapours or spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.	P243	Take precautionary measures against static discharge.
P271 Use only outdoors or in a well-ventilated area.	P261	
P271 Use only outdoors or in a well-ventilated area.	P264	Wash hands thoroughly after handling.
D272 Avoid release to the environment	P271	Use only outdoors or in a well-ventilated area.
r 2/3 Avoid felease to the chynolinent.	P273	Avoid release to the environment.
P280 Wear protective clothing as detailed in SDS Section 8.	P280	Wear protective clothing as detailed in SDS Section 8.
Degrange and Degrange Statement	Dagnanga anda	Degrange Statement
Response code P101 Response Statement If medical advice is needed, have product container or label at hand.	<del>-</del>	<u>-</u>
, <u>1</u>		
P312 Call a POISON CENTER or doctor/physician if you feel unwell. P331 Do NOT induce vomiting.		<u> </u>
P391 Collect spillage.		<b>C</b>
P301 + P310 F SWALLOWED: Immediately call a POISON CENTER or doctor/physician.		
		•
P303 + IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. P361+P353 Rinse skin with water/shower.		•
F301+F333 Kinse skill with water/shower.  IF INHALED: Remove to fresh air and keep at rest in a position comfortable for	F 301+F 333	
P304 + P340 breathing.	P304 + P340	• •
P308 + P313 IF exposed or concerned: Get medical advice/ attention.	D200 + D212	
P332 + P313 If skin irritation occurs: Get medical advice/ attention.		
P362+P364 Take off contaminated clothing and wash before reuse.		
P370 + P378 In case of a fire use CO2, Dry Chemical or Foam.		· · · · · · · · · · · · · · · · · · ·
13/0 + 13/6 In case of a fire use CO2, Dry Chemical of Foain.	F3/0 + F3/6	in case of a fire use CO2, Dry Chemical of Foam.
Storage Code Storage Statement	Storage Code	Storage Statement
P405 Store locked up.		
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.	P403 + P233	•
P403 + P235 Store in a well-ventilated place. Keep cool.	P403 + P235	1 1

## **Section 3: Composition/Information on Ingredients**

Name Concentration % CAS Number Petroleum Naptha Hydrotreated Light > 60 64742-49-0

Note: Manufacturer has provided full ingredient information for assessment.

## **Section 4: First Aid Measures**

Rinse cautiously with water for several minutes. Remove contact lenses, **Eyes:** 

if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice/attention.

Skin: Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. If skin irritation occurs: Get medical advice/

attention.

**Ingestion:** If medical advice is needed, have product container or label at hand.

Call a POISON CENTER or doctor/physician if you feel unwell.

Do NOT induce vomiting.

**Inhalation:** Remove from contaminated area. Get medical advice/attention if you

feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms:

**Ingestion:** Nausea, vomiting & sweating with burns to the mouth & oesophagus may occur.

Unconciousness may follow

**Inhalation:** The vapour is discomforting to the upper respiratory tract and lungs and may be

harmful if inhaled. Dizziness & shortness of breath occur from mild poisoning.

Skin: Possible irritation on sensitive skin

Eye: Irritation

FOR FURTHER INFORMATION CONTACT (24 hours) THE NATIONAL POISON CENTRE: 0800 POISON [764 766]

Section 5: Fire Fighting Measures

**Hazard Type** Flammable Liquid

Oxides of Carbon when burned. **Hazards from products** 

**Suitable Extinguishing** 

media

CO2, Dry Chemical or Foam. Water spray or Fog (for large fires only)

**Precautions for firefighters** 

and special protective clothing

Full respiration equipment is advisable. Evacuate area.

3Y **HAZCHEM CODE** 

Section 6: Accidental Release Measures

**Land Spills or Leaks:** 

Wear protective clothing as detailed in Section 8. Remove all unnecessary personnel. Eliminate ignition sources. Contain spill with inert material & place in recovery containers for disposal. Avoid release

to the environment.

**Waste Disposal Method:** Dispose through Licensed Disposal Company

## **Section 7: Handling And Storage**

### Handling

- Keep out of reach of children.
- Read label before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames and hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical, ventilating, and lighting.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid release to the environment.
- Wear protective clothing.
- Use personal protective equipment as required.

### **Storage:**

- Store in a well-ventilated place. Keep cool.
- Keep out of reach of children.
- Store locked up.
- Protect containers against physical damage and check regularly for leaks.

## Section 8: Exposure Controls/Personal Protection

## WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

No ingredients have exposure limits

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices Nov 2023 14TH EDITION.

#### **Personal Protection Equipment**







**Engineering Controls:** Local exhaust ventilation usually required

**Eye / Face Protection:** Safety glasses with a side shield or a full-face shield should be worn.

**Body Protection:** Overalls / PVC apron

**Respiratory Protection:** Self contained Breathing apparatus required if using in a confined space

# **Section 9: Physical And Chemical Properties**

Appearance	Liquid
Colour	Water white
Odour	Solvent Odour
Odour Threshold	Not available
pН	Not applicable
<b>Boiling Point</b>	85°C
Melting Point	Not available
Freezing Point	Not available
Flash Point	-22 <sup>o</sup> C (cup closed)
Flammability	Flammable
Upper and Lower Explosive	1% to 6.0%
Limits	
Vapour Pressure	<35
Vapour Density	4.8
Specific Gravity	0.70 g/cm <sup>3</sup> @ 25 <sup>0</sup> C
Solubility in Water	Insoluble
Partition Coefficient:	Not available
Auto-ignition Temperature	280°C
<b>Decomposition Temperature</b>	Not available
Kinematic Viscosity	Not available
<b>Particle Characteristics</b>	Not applicable
Volatiles	100%

## **Section 10: Stability And Reactivity**

**Conditions Contributing to** 

**Instability:** 

Not available.

**Incompatibility:** Sources of heat &/or ignition, Oxidising agents.

**Hazardous Decomposition** 

**Products:** 

Carbon Dioxide & Water

**Conditions Contributing to Hazardous Polymerization** 

Will not polymerise

# **Section 11:** Toxicological Information

### **Acute Effects:**

Swallowed	This product is not classified as acutely toxic.
Dermal	This product is not classified as acutely toxic.
Inhalation	This product is not classified as acutely toxic.
Eye	This product is not classified an eye irritant/corrosive.
Skin	Causes skin irritation.

#### **Chronic Effects:**

Carcinogenicity	This product is not classified as carcinogenic.
Reproductive Toxicity	Suspected of damaging fertility or the unborn child.
Germ Cell	This product is not classified as mutagenic.
Mutagenicity	
Aspiration	May be fatal if swallowed and enters airways.
STOT/SE	May cause drowsiness or dizziness.
STOT/RE	This product is not classified as STOT RE.

### **Section 12: Ecological Information**

Toxic to aquatic life with long lasting effects

**Environmental Precautions:** Do not allow product to wash into waterways.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

# **Section 13: Disposal Considerations**

Recover and recycle product whenever possible. Dispose of waste in accordance with Regional Authority or local council bylaws.

Ensure empty containers are vented and dry. Residues may cause an explosion hazard. Do not puncture, cut or weld un-cleaned drums. Send clean dry drums to recycler or metal scrap re-claimer. Do not use empty drums for storing other products.

### **Section 14: Transport Information**

This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2020 and SNZ HB 5433:2021



#### Road, Rail, Sea and Air Transport

UN No	1993
Class - Primary	3
Packing Group	II
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Marine Pollutant	Yes
Special Provisions	If the product's individual container is below 1L, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

# Section 15: Regulatory Information

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval Code: Cleaning Products (Flammable) - HSR0002528

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	100L (>5L), 250L (<5L), 50L open
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	250L
Emergency Response Plan	1000L
Secondary Containment	1000L
Fire Extinguishers	$2 \times 250L$
Restriction of Use	None

### **Section 16: Other Information**

### Glossary

EC50Median effective concentration.EELEnvironmental Exposure Limit.EPAEnvironmental Protection Authority

HSNO Hazardous Substances and New Organisms.

HSW Health and Safety at Work.

LC<sub>50</sub> Lethal concentration that will kill 50% of the test organisms inhaling or

ingesting it.

LD<sub>50</sub> Lethal dose to kill 50% of test animals/organisms.

LEL Lower explosive level.

OSHA American Occupational Safety and Health Administration.

TEL Tolerable Exposure Limit.

TLV Threshold Limit Value-an exposure limit set by responsible authority.

UEL Upper Explosive Level WES Workplace Exposure Limit

#### References:

- 1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
- 2. Workplace Exposure Standards and Biological Exposure Indices Nov 2023 14th edition.
- 3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
- 4. Transport of Dangerous goods on land NZS 5433:2020
- 5. HSW (Hazardous Substances) Regulations 2017

#### Disclaimer

Marketing Chemicals Ltd has taken care in compiling this information. No liability is accepted directly or indirectly from its application as conditions of use are outside the Company's control. End users are obliged to conform to relevant Local Government regulations.

For General Information: Marketing Chemicals Ltd,

Phone: +64 (09) 634 3862 / +64 274 340990

Fax : +64 (09) 634 3864

Issue Date: 29 August 2024 Review Date: 29 August 2029

End of Safety Data Sheet.